
SUBMITTAL INFORMATION



Angle Key Flange Meter Valves - (FV13-676W-NL style)



VALVE SIZE	Service Line Size Inlet	Meter Size Outlet	Length	Неіднт	Approx. Wt. Lbs	Part Number	✓ Submitted Iteм(s)
1-1/2"	2"	1-1/2"	1-1/4"	3"	6.2	FV13-676W-NL	

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (ASTM B584, UNS C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Certified to NSF/ANSI Standard 61 and NSF/ANSI Standard 372 where applicable
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS C83600, 85-5-5-5)
- Padlock wing for locking valve in closed position
- Flat drop-in gaskets included
- Meets 80 PSI pressure requirement of AWWA Standard C800

Optional Meter Support Brackets. Add "-MSB" to end of part number

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.

The Ford Meter Box Company, Inc. P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487 Overseas Fax: 260-563-0167 www.fordmeterbox.com 10/12/1	Submitted By:
--	---------------